

Compatibility Chart

Reader / Panel	Features			Card Option			Features					Temp.	Slave Reader		Enroll. reader	
	WGND	PSU	IP-65	ID	MF	HID	Keypad	FP	Face	Displ.	Ether.	F	FR1200	KR	ZK4000	CR10
F6 reader	out	OPT	-	OPT	OPT	-	+	+	-	B/W	-	32-113	-	-	-	-
F18 reader, incl. PSU	in/out	+	-	+	OPT	OPT	+	+	-	Color	+	32-113	OPT	OPT	+	+
US-700 reader	in/out	OPT	-	+	OPT	OPT	+	+	-	B/W	+	32-113	OPT	OPT	+	+
F707 reader	out	OPT	-	-	-	-	+	+	-	B/W	+	32-113	-	-	+	+
MB700 reader, incl. PSU	in/out	+	-	+	OPT	OPT	Touch	+	+	Color	+	32-113	-	OPT	+	+
SC403 reader	in/out	OPT	-	+	OPT	OPT	+	-	-	B/W	+	32-113	-	OPT	-	+
TF1600 reader, incl. PSU	in/out	+	+	+	OPT	-	-	+	-	B/W	+	-40-113	OPT	OPT	+	-
TF1700 reader, incl. PSU	in/out	+	+	+	OPT	-	+	+	-	B/W	+	32-113	OPT	OPT	+	-
IN-BIO Panel / *Bundle	in	-/+	-	-	-	OPT*	-	-	-	-	+	32-113	+	+	+	-
C-3 RFID Panel / *Bundle	in	-/+	-	-	-	OPT*	-	-	-	-	+	32-113	-	+	-	+
FR1200 slave reader FP, Card	-		+	+	-	-	-	+	-	-	-	32-113	-	-	-	-
KR series slave reader, Card	out		+	+	-	-	-	-	-	-	-	32-113	-	-	-	-
ZK4000 enroll. USB, FP, Card	USB		-	-	-	-	-	+	-	-	-	32-113	-	-	-	-
CR10E enroll. USB, Card	USB		-	+	-	-	-	-	-	-	-	32-113	-	-	-	-
[*Bundle]	Includes Inbio or C3 Panel controller, Metal Case and Power Supply (PS).															
[PS]	Power Supply 12V DC: 1.5A or 3A. Included with a reader [+] or available for purchase [OPT]															
[ID]	Standard 26 bit Generic 125 kHz Proximity Card															
[+]	Default/ Stock OR [-] - Not Available															
[OPT]	Special Order: 4-6 weeks delivery [OPT*] Compatible with HID and other Card readers with Wiegand Output.															

- F6** The only ZKA reader without Ethernet port.
- F18-ID** Indoor, Color Display, Keypad, Fingerprint, Card reader, Ver.10 Algorithm
- US700** ID – Indoor, horizontal, B/W display, Keypad, Fingerprint, Card reader; Ver.10 Algorithm.
- F707** Indoor, Vertical, B/W display, Keypad, Fingerprint, NO Card reader options.
- MB700** Indoor, Vertical, TOUCH screen, FACE, Fingerprint, Card reader; Ver.10 Algorithm.
- SC403** Indoor, B/W display, Keypad & Card reader only, KR series compatible for secured connection;
- TF1600** IP-65 Rated, Vertical, Fingerprint, Card reader. The only ZK reader working in Operating Temperature: -40° to 113° F (-40° to 45° C).
- TF1700** IP-65 Rated, Vertical, Keypad, Fingerprint, Card reader
- FR1200** IP-65 Rated, Fingerprint, Card, Slave reader to InBio-Panel and Standalone Readers: F18, TF1700, US700;
- KR series** IP-65 Rated, Card Slave reader to C3- Panel C3Panel and Standalone readers: F18, SC403, MB700, TF1700, US700.